

3.28 PRIMAFLEX KLIPP HT500

Temperature range -20 °C to 500 °C



Description

Flexible clamping profile hose with a layer made of specially coated high-temperature textile fabric, clad on one side with stainless steel foil and with galvanized steel clamping profile. Highly suitable for suction of hot gaseous media at high temperatures.

Available in our online shop

Properties

- Superior temperature resistance
- Good compressibility
- Good vacuum resistance
- Flexible
- Flameproof
- Small bending radii
- Only suitable for continuously bent motion under certain circumstances

Application ranges

Suction technology

Length

Standard lengths: 2 - 10 m. According to specifications.

Further informations

Color: red.

Clamping profile also in VA (1.4512, 1.4301).

Short-term exposure +550 °C

TECHNICAL SPECIFICATIONS

Inner-Ø (mm)	Bending radius (mm)	Vacuum (bar)	Weight (kg/m)	Length (m)	Article-No.
80	48	0,228	1,53	2 - 10	6157080
90	54	0,209	1,72	2 - 10	6157090
100	60	0,168	1,98	2 - 10	6157100
110	66	0,139	2,17	2 - 10	6157110
120	72	0,118	2,2	2 - 10	6157120
125	75	0,105	2,45	2 - 10	6157125
140	84	0,088	2,73	2 - 10	6157140
150	90	0,076	2,92	2 - 10	6157150
160	96	0,067	3,11	2 - 10	6157160
180	108	0,052	3,52	2 - 10	6157180
200	120	0,042	3,9	2 - 10	6157200
225	158	0,035	3,26	2 - 10	6157225
250	175	0,029	3,62	2 - 10	6157250
300	210	0,019	4,32	2 - 10	6157300
350	245	0,015	5,03	2 - 10	6157350
400	280	0,011	5,76	2 - 10	6157400
450	360	0,009	6,46	2 - 10	6157450
500	400	0,007	7,17	2 - 10	6157500
550	440	0,006	7,87	2 - 10	6157550
600	480	0,005	8,58	2 - 10	6157600
700	560	0,004	9,98	2 - 10	6157700
800	640	0,003	11,39	2 - 10	6157800
900	720	0,002	12,8	2 - 10	6157900